

LED CLASSIC Candle E14



1

NEW

REDUCTION
E27 TO E14
pag. 128



E14 / CANDLE / FILAMENT

n°	Power Volt	Base	W	Life (u/h)	Temp (°K)	Ra v	Beam (cd)	Light (lm)	Angle (°)	Beam (%)	Beam (mm)	Beam (mm)	Beam (mm)	Beam (mm)	ENERGY	Icon
1 MM 05243	230	E14	3.2	15000	2700	80	-	220	330	10 - 100	-	-	113	35	A++	Power Icon

*PHASE CUT / PAR COUPEURE DE PHASE



1



2



E14 / DECORATIVE RING

n°	Power Volt	Base	W	Life (u/h)	Temp (°K)	Ra v	Beam (cd)	Light (lm)	Angle (°)	Beam (%)	Beam (mm)	Beam (mm)	Beam (mm)	Beam (mm)	COLOUR
1 MM 05789	-	-	-	-	-	-	-	-	-	-	-	30	27	-	GOLD
2 MM 05790	-	-	-	-	-	-	-	-	-	-	-	30	27	-	SILVER



1

E14 / CANDLE / FILAMENT / TIP / GOLD

n°	Power Volt	Base	W	Life (u/h)	Temp (°K)	Ra v	Beam (cd)	Light (lm)	Angle (°)	Beam (%)	Beam (mm)	Beam (mm)	Beam (mm)	Beam (mm)	ENERGY	Icon
1 MM 07173	230	E14	3	15000	2700	80	-	210	360	N0	-	-	118	35	A+	Power Icon GOLD